



1: SPORTING REGULATIONS - GENERAL

1.1: TITLE & JURISDICTION:

The **750 FORMULA CHAMPIONSHIP** is organised and administered by the 750 Motor Club Ltd in accordance with the General Regulations of the Royal Automobile Club Motor Sports Association (incorporating the provisions of the International Sporting Code of the FIA) and these Championship Regulations.

1. **MSA Championship Permit No: CHR2015/R020**
2. **MSA Championship Grade: D.**
3. **Race Status: Clubmans / National B.**

1.2: OFFICIALS:

1. **Co-Ordinator:** G.Groombridge, The Conservatory Suite, Donington Park, Castle Donington, Derbyshire, DE74 2RP

☎ 01332 814548; ✉ giles@750mc.co.uk.

2. **Eligibility Scrutineer:** R.Blackmore

3. **Championship Stewards:**

R.Knight K. Messer I.Sowman

1.3: COMPETITOR ELIGIBILITY:

1 Entrants must:

- (a) be fully paid up valid membership card holding members of the 750 Motor Club and
- (b) be Registered for the Championship and
- (c) be in possession of a valid MSA Entrants Licences.

2 Drivers and Entrant/Drivers must:

- (a) Be current Members of the 750 Motor Club and
- (b) be Registered for the Championship and
- (c) be in possession of valid Competition (Racing) National B Licence, as a minimum
- (d) A professional driver, in possession of a valid Licence (featuring an E.U. flag) and medical, issued by the ASN of a member country of the European Union, or comparable country. ((H)26.2.1. applies)

(e) If participation in the Championship requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the Championship. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.

3. All necessary documentation must be presented for checking at all rounds when signing-on.

1.3.4: COLLEGE CLASS ELIGIBILITY:

1. The College Class will run as Class C of the Championship.
2. Colleges will nominate one representative who will register as Entrant of the vehicle and will require an MSA Entrants Licence. The registration fee of £120 is payable to the 750 Motor Club upon registration of the vehicle.
3. The nominated representative of the College must be a fully paid up membership card holding member of the 750 Motor Club Ltd.
4. The car registered by a College may be entered by any driver authorised by that College.
5. All drivers must hold a valid MSA National B (or higher grade) Race Licence or be a professional driver in possession of a valid Licence (featuring an E.U flag) & medical issued by the ASN of a member country of the European Union (MSA Regulation H26.2.1.)

1.4: REGISTRATION:

1. All competitors must register for the championship by returning the Registration Form with the Registration Fee to the Coordinator prior to the Final Closing date for the first round being entered.
2. The Registration Fee is £120 payable upon registration.
3. Registration numbers will be the permanent Competition number for the Championship.

1.5: CHAMPIONSHIP ROUNDS:

The **750 FORMULA CHAMPIONSHIP** will be contested over the following rounds:

Date	Circuit	Round/s
28/29 March	Donington Park	2
25/26 April	Brands Hatch	2
20/21 June	Cadwell Park	2
18/19 July	Anglesey	2
23 August	Silverstone Int	2
12/13 September	Snetterton 300	2
27 September	Mallory Park	2

1.6: SCORING:

1. Points will be awarded to Competitors listed as classified finishers in the Final Results as follows:- 25; 22; 20; 18; 16; 14; 12; 11; 10; 9; 8; 7; 6; 5; 4; 3. All other finishers 2. All starters who fail to finish 1.

2. The totals from all qualifying rounds run (excluding any races which are abandoned and which are not replaced) less 2 will determine the final championship points positions.

3. Ties shall be resolved using the formula in (W)1.3.4. in the current MSA Yearbook.

4. Where the race distance has been reduced (2.6.) it shall still count as a full points scoring round.

5. Competitors not registered for the Championship may be permitted on an individual round basis and will:

(a) be deemed "Guest Competitors"

(b) not score points and for the purpose of points scoring will be ignored

(c) qualify for Event awards

(d) comply with the eligibility criteria as prescribed in Article 1.3. above, with the exception of 1.3.1. (b) and 1.3.2. (b), as appropriate

6. Additionally, drivers who, during the previous 5 years have not finished in the top 3 in any 750 Formula race, the top 6 in the end-of-year positions or 1st in class B in the end-of-year positions, may register to score points in Class B as well as the overall championship. Any driver registered for Class B who finishes in the top 3 in any 750 Formula race will immediately become ineligible for Class B. For the purpose of the Class B Championship positions any points they have score to that point will be dropped, but this will not affect any other competitors, i.e. the Class B Championship points will remain unaffected.

7. Cars registered for Class C will only score points in Class C, awarded as per 1.6.1.

8. Where two drivers are registered in the Team Challenge and are sharing a car, their points scored (as per 1.6.1) will be combined and they will compete for the Team Challenge Awards as per 1.7.3. Each driver must contribute at least 4 scores to the team total.

1.7: AWARDS:

1. All awards are to be provided by the Organising Club unless agreed otherwise.

2. Per Round: Trophies to 1st, 2nd and 3rd in each class.

3. Championship: Trophies, subject to a minimum of 5 race starts, to:-

1st, 2nd, 3rd, 4th, 5th & 6th overall.

1st, 2nd & 3rd in class B.

1st in Class C.

Best Prepared car.

Highest placed non race winner.

Highest placed driver in his first year in the championship.

Highest placed driver in a car of his own design and construction in its first season of racing.

Season's best qualifier, calculated using the same points system and same number of qualifying rounds as the main championship (Will Johnston Jr. Trophy).

Team Challenge trophy for the team with the highest scores as described in 1.4.8.

4. Presentations: Awards will be presented at the end of each event, and/or at the end of the Championship at the designated presentation ceremony.
5. Entertainment Tax Liability: {deleted}
6. If Provisional Results or Championship Tables are revised after any presentations and these revisions affect the distribution of awards the Competitors concerned must return them to the organisers in good condition within 7 days.

2: CHAMPIONSHIP EVENT MEETINGS & RACE PROCEDURES

1. ENTRIES:

1. Competitors are responsible for sending in correct and complete entries with the correct entry fee prior to the closing date for entries before each event.
2. Incorrect or incomplete entries (Including Driver to be Nominated Entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Meeting Organiser receives the missing or corrected information or fee.
3. Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Meeting Organisers in writing. D25.1.12. applies.
4. The Entry Fee for each event shall be specified in the SRs and on the entry form.
5. Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.

2. BRIEFINGS: Organisers should notify Competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

3. QUALIFICATION PRACTICE:

1. Should any Practice session be disrupted the Clerk of the Course shall not be obliged to resume or re-run the session; the decision of the Clerk of the Course shall be final.
2. Each driver shall complete a minimum of 3 laps in the car to be raced, and in the correct session, in order to qualify (MSA Regulations Q4.5).

4. RACES: Should any race be disrupted the Clerk of the Course shall not be obliged to resume or rerun the race ((Q)5.4.) (1.6.4. above applies)

5. STARTS:

1. All cars will be released to form up on the grid prior to the start in formation as specified on the grid sheet.
2. The start will be via Standing start. The minimum Countdown procedures/audible warnings sequence shall be:-
 - I. 1 minute to start of Green Flag/Pace Lap - Start Engines/Clear Grid.
 - II. 30 Seconds - Visible and audible warning for start of Green Flag/Pace Lap.
 - III. A five second board will be used to indicate that the grid is complete.
 - IV. The red lights will be switched on five seconds after the board is withdrawn.
3. Any car removed from the grid after the 1 minute stage or driven into the pits on the Green Flag lap shall be held in the pitlane and may start the race after the last car has passed the startline or pitlane exit, whichever is the later to take the start from the grid.
4. Any driver unable to start the Green Flag/Pace lap or start are required to indicate their situation as per MSA Regulation (Q)12.13.2. In addition any driver unable to maintain grid positions on the Green Flag Lap, to the extent that ALL other cars are ahead of them, may complete the Green Flag lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
5. In the event of any starting lights failure the Starter will revert to use of the National Flag.

6. SESSION RED FLAG: Should the need arise to stop any race or practice, RED LIGHTS will be switched on at the Startline and RED FLAGS will be displayed at the Startline and at all Marshals Signalling Points around the Circuit. This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pit lane, during practice, and to the starting grid area, during a race, unless otherwise directed by officials. Cars may not enter the Pits unless directed to do so. Work on cars already in the Pits must cease when a race is stopped.

7. PITS, PADDOCK & PITLANE SAFETY:

- 1 Pits & Paddock: Competitors must ensure that the MSA, Circuit Management and Organising Club Safety Regulations are complied with at all times.
2. Pitlane: The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all Drivers to take all due care and respect the pit lane speed limits.
3. Refuelling: May only be carried out in accordance with the MSA General Regulations, the Organising Club Regulations, Circuit Management Regulations and the SRs or Final Instructions issued for each Circuit/Meeting.
4. Speed Limit: Pit Lane Speed Limit will be 60 km/h.

8. RACE FINISHES: After taking the Chequered Flag drivers are required to:

- I. progressively and safely slow down
- II. remain behind any competitors ahead of them,
- III. return to the Pit Lane Entrance/Paddock Entrance as instructed,
- IV. comply with any directions given by Marshals or Officials
- V. keep their helmets on and harnesses done up while on the circuit or in the pitlane.

9. RESULTS: All Practice Timesheets, Grids, Race Results are to be deemed Provisional until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures. (MSA regulation (D)26.3.)

10. TIMING MODULES: The 750 Motor Club utilises AMB transponder-based timing and competitors must have a compatible transponder fitted and working and advise the race organisers of its number prior to the event. The transponder is a TRANX 260 Direct Powered and is available from HS Sports Ltd – 01260 275708.

11. QUALIFICATION RACES: If any event is oversubscribed the Organising Club may at their discretion run Qualification Races.

12. OPERATION OF SAFETY CAR: {deleted}

13. ONBOARD CAMERAS: {deleted}

3: SPECIFIC CHAMPIONSHIP REGULATIONS

In the event of any rounds being oversubscribed the Organising Club may, in liaison with the Championship Coordinator, at their discretion run Qualification races as per 2.11 of these regulations. Alternatively at double header race meetings, should there be sufficient space within the timetable, the Organising Club may divide the grid after qualifying into 3 separate Groups. The Groups will then form 3 races whereby each competitor participates in two races. All 3 races will be eligible for full championship points.

4: SPECIFIC CHAMPIONSHIP PENALTIES:

In accordance with Section C of the current MSA Yearbook

4.1: INFRINGEMENT OF TECHNICAL REGULATIONS:

1. Arising from post practice Scrutineering or Judicial Action:
Minimum Penalty: The provisions of MSA Regulations: C3.3.
2. Arising from post race Scrutineering or Judicial Action:
Minimum Penalty: The provisions of MSA Regulations: C3.5.1 (a) and (b).
For infringements deemed to be of a more serious nature the Clerk of the Course will invoke the provisions of Regulation C3.5.1 (c).

4.2: ADDITIONAL SPECIFIC CHAMPIONSHIP PENALTIES

5: TECHNICAL REGULATIONS

5.1: INTRODUCTION:

The following Technical Regulations are set out in accordance with the MSA specified format and it should be clearly understood that if the following texts do not clearly specify that you can do it, you must work on the principle that you cannot.

STANDARD: The word 'standard' used within these technical regulations as a description of components is to be interpreted as per 'Standard Part' defined in Section B – Nomenclature & definitions in the MSA Blue Book. Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance. It applies to the specified component/s from the manufacturer's parts list for the model / engine shown on the entry form or registration form. No modifications permitted beyond the repair or adjustment processes specifically specified by the manufacturers' workshop manual or microfiche.' Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance.

5.2: GENERAL DESCRIPTION:

The **750 FORMULA CHAMPIONSHIP** is for Competitors participating in two-seater, front or rear engined, open or closed sports-racing cars.

5.3: SAFETY REQUIREMENTS:

The following Articles of MSA Section K Safety Criteria Regulations will apply: K1.6.4 or K1.5; K2.1.3, K2.1.4; K3 – K14. Extinguishers must comply with MSA regulation K 3.1.2 a). Seat belts must be FIA homologated in accordance with Q19.14.2. Towing eyes to be in accordance with MSA Regulation Q19.1.3; (note the tow eye may be of either a suitable rigid or flexible material).

5.4: GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS:

All cars must comply with the requirements of sections J and Q19. of the current MSA Yearbook. All vehicles must be of sound construction and mechanical condition and be well maintained. As a minimum, two mirrors must be fitted, each with a minimum surface area of 50 sq cms and giving a clear view to the rear, one on each side of the centreline of the vehicle.

5.5: CHASSIS:

1. The chassis must be constructed from metal. Chassis components must not be constructed using carbon fibre, kevlar or composites containing these materials.
2. At the rear of the driver/passenger space, the chassis must be at least 76.2cm (30in) wide to the inside of the chassis panels such that it must be possible to drop into the driver/passenger space through the driver/passenger space opening at right angles to the longitudinal centre line of the car an inverted 'U' shaped member with legs 76.2cm (30in) apart (measured over the outside of the legs) held vertically so that the difference in height of the legs does not exceed 76mm (3in) when one of the legs is on the lowest floor level.
3. The longitudinal centre line of the driver's seat must be at least 17.8cm (7in) from the longitudinal centre line of the car.
4. The passenger space, must be large enough to accept fully a trapezoidal volume with front and rear faces lying on two planes, both perpendicular to the longitudinal centre line of the car and separated by 70cm (28in). The front face should be a rectangle measuring 15cm (6in) wide and 25.4cm (10in) high. The rear face should be a rectangle measuring 27.9cm (11in) and 25.4cm (10in) high.

Nothing may be located in the passenger space except a fire extinguisher and any ballast required to comply with the minimum weight regulation.

5. The driver/passenger space must be clear of and not divided by any chassis members other than those forming the propshaft tunnel in front engined cars, roll over bar braces or for location of the gear change linkage in rear engined cars. Cars that do not have a transmission tunnel may have a vertical, longitudinal bulkhead between the driver and the passenger space. This must be no more than 2.5cm wide and no more than 30cm high.

5.6: BODYWORK:

1. Modifications Permitted:

1. Cockpit:

- i) There must be only one cockpit opening to serve both driver and passenger space. The opening must be large enough to accept, with its longest side transversely at the rear of the opening, a horizontal quadrilateral frame with hinged joints, one side 81.3cm (32in) long, two opposite sides 45.7cm (18in) and the fourth side 63.5cm (25in). In checking, neither rear internal angle of the quadrilateral frame may exceed 92° and neither front internal angle may exceed 120°. (See appendix 6.1 for diagram.)
- ii) In checking the cockpit opening any obstruction caused by the bracing members for a roll over bar may be ignored.
- iii) Closed cars must provide similar unobstructed area at drivers/passenger shoulder level.

2. Passenger space: Any cover over the passenger space and/or forming an extension to the windscreen alongside the driver must be constructed only of supple and flexible fabric and must be easily removable, or if of a rigid material to comply with Q19.2.3.

3. Interior: As defined above.

4. Exterior:

- i) Aerofoil devices ahead of the front wheels are permitted, but must be below the top of the front wheel rims and not exceed in width the centre line of the front tyres. They must form a continuous part of the bodywork.
 - ii) A rear aerofoil is permitted. Chord must not exceed 30cm (11.8in). Maximum width to be full body width or outermost track whichever is the greater.
 - iii) Any rear aerofoil or bodywork must not overhang the rear of the vehicle by more than 70cm (27.5in) measured from the centre line of the rear wheels. The height of any bodywork or aerofoil must not exceed 90cm (35.4in) with the driver aboard, measured from the ground, excluding safety roll over bars, or bodywork of closed cars between the centre line of the front and rear wheels.
 - iv) Any forward facing horizontal splitter attached to the lowest edge of the front bodywork may not exceed the maximum overall width of the wheels or bodywork whichever is the greater.
- 5. Silhouette:** Not applicable.
- 6. Ground Clearance:** As per MSA regulation J5.20.11.

2. Modifications Prohibited:

1. **General:** Any in contravention of 5.6.1.
2. **Interior:** Any in contravention of 5.6.1.
3. **Exterior:** There shall be nothing to obstruct wholly the driver's sight from the normally seated position of another car to the front or either side.
4. **Silhouette:** Any in contravention of 5.6.1.
5. **Ground Clearance:** Any in contravention of 5.6.1.

5.7: SUSPENSIONS:

Suspension systems are free, subject to MSA regulations and with the following exceptions:
Suspension components must not be constructed using carbon fibre, kevlar or composites containing these materials.

5.8: ENGINE:

The engine must be a Fiat FIRE engine of 1108cc capacity and the only parts permitted are those originally fitted to the 1108cc FIRE engine or pattern parts to the same design and made of the same materials as the standard Fiat part fitted to the engine specified above.

The cylinder head must be a standard FIAT component bearing the casting number 46400108, located above number 2 exhaust port.

Two camshaft cover bolts (one on each side of the engine) must be drilled to allow the engine to be sealed by Scrutineers.

Two sump bolts (one on each side of the engine) must be drilled to allow the engine to be sealed by Scrutineers.

The only modifications permitted are those listed below. It is the competitor's responsibility to ensure that no prohibited modifications have been carried out whether or not they have assembled the engine.

1. Modifications Permitted:

- i) The standard ferrous Fiat flywheel must be used, but can be modified by the removal of material only.
- ii) Lubrication system is free and may be either dry or wet sump.
- iii) Clutch Pressure plate must have a minimum diameter of 180mm or be as is/as has been fitted as standard to a Fiat FIRE engine; friction plate is free.
- iv) Rebore permitted up to + 0.6mm using standard pattern pistons only. The wear allowance on bores is 0.2mm measured at the maximum point of piston ring travel.
- v) Replacement of valve guides and valve seats is permitted with parts of standard pattern and material. Valve seat inserts must not protrude beyond the combustion chamber surface.
- vi) Metal may be removed from the crankshaft, pistons and connecting rods for balancing purposes only. In the case of pistons and connecting rods, one component must be left with completely original machining. The crankshaft can be balanced by local grinding or spot drilling only and at least one counterbalance weight must remain as standard.
- vii) Facing of the head and block is permitted within the constraints of the standard cam belt and pulley system, no other modifications to the cylinder head are permitted.
- viii) Removal of the original mounting lugs from the outside of the block is permitted for the sole purpose of facilitating engine installation.
- ix) The only permitted camshaft is the item supplied by Newman Cams (see 6.2 of these regulations); the serial number of the camshafts must be notified to the 750 Motor Club on the championship registration form. Valve springs and shims are free but only single springs may be used and spring seats may not be machined. Offset dowels or Vernier camshaft pulley are permitted.
- x) The cylinder head may be drilled and tapped (or helicoiled) and plugged to blank the water take-off for the inlet manifold.
- xi) Helicoil inserts are permitted to repair damaged threads in cylinder block and cylinder head.
- xii) Three angle valve seats are permitted on the valve seat inserts. The valves must retain the standard Fiat shape and profile.
- xiii) Non-standard external fasteners on engine block and head are allowed. For clarity, this is any fastener that can be accessed with the sump and cam cover fitted normally.
- xiv) Core plugs may be retained by mechanical fastening.
- xv) One cam cover retaining bolt and one sump retaining bolt must be drilled to accept locking wire which may be used by scrutineers to seal the engine. The drilled bolts must be located on the engine in such a way as to prevent the cam cover and sump from being removed in the event of the engine being sealed.
- xvi) The standard method of locating the crank pulley to the crank may be modified for the sole purpose of locating the pulley more securely.

2. Modifications Prohibited:

Any not listed in 5.7.1 including but not limited to:

- Polishing or removal of metal from the inlet or exhaust ports.
- Polishing, removal or addition of material from/to the combustion chamber.
- Polishing of connecting rods or any other internal components.
- Reprofilling of camshafts or regrinding of camshafts from blanks.

- Use of electric water pumps; the standard water pump must be used
- Lightening of engine components with the sole exception of the flywheel.

Other engine regulations

3. **Location:** Front or rear.
4. **Oil/Water cooling:** Free within overall periphery of bodywork.
5. **Induction Systems:** Carburetion shall be by only one carburettor choke. Forced induction, fuel injection and external slide throttles are prohibited. The carburettor may not be adjusted while the vehicle is in motion either by mechanical or electrical means.
6. **Exhaust systems:** Exhaust systems including manifold are free but must comply with MSA regulations J 5.16.1 – 5.16.5.
7. **Ignition systems:** Only ignition systems that use only one trigger, inside the distributor or external, to initiate the low tension current will be permitted. Any system that requires more than one sensor or input to provide another signal/voltage for any electronic/microprocessor control system is not permitted.
8. **Fuel delivery systems:** Free.

5.8: SUSPENSIONS:

Suspension systems are free, subject to MSA regulations.

5.9: TRANSMISSIONS:

Gear selection, clutch operation and throttle operation must be purely mechanical and solely under direct control of the driver. The gear linkage and clutch system must be purely mechanical (hydraulic clutch systems are permitted). No electrical connections, switches or sensors may operate on any part of the clutch or gear controls or linkages.

Automatic transmission, torque biasing, locked or limited slip differentials are all prohibited. The use of any electronic traction control system is prohibited.

Cars must have an operable reverse gear capable of being engaged by the driver whilst normally seated.

A. Live rear axle

For all cars not using a standard Fiat transaxle, a bevel-driven, live rear axle from a series production car must be the sole means of driving the rear wheels.

1. **Permitted modifications:** It is permitted to add brackets for mounting suspension and/or braking systems. The axle may be modified to accept longer or shorter half shafts.
2. **Prohibited modifications:** Magnesium alloy bell housing, gearbox casing and tailshaft are prohibited.
3. **Transmissions & Drive ratios:** Axle ratios are free. For cars not using a Fiat transaxle, gearbox ratios are free and the gearbox must not contain more than four forward gears and one reverse

B. Fiat transaxle

As an alternative a standard Fiat transaxle can be used but must be the sole means of driving the rear wheels.

A system of gear ratio validation is applied which uses the recognised MSA scrutineer's seal. A hole must be drilled at the gearbox casting joint to enable locking wire to be passed through. When gear ratios are checked and passed as being correct by a scrutineer the gearbox will be sealed by this method. If at any time this seal is broken the ratios must be rechecked. No points may be scored by a driver whose car has unchecked ratios.

1. **Permitted modifications:** A standard Fiat transaxle must be used. It must contain an operable reverse gear and 5 forward gears capable of being engaged by the driver whilst normally seated. The transmission must be mounted to the engine in its original *plane* such that the gearbox mainshaft axis must remain in line with the engine main bearings axis. The gearbox may be rotated relative to the engine about the crankshaft axis; a spacer of up to 12mm may be used between engine and gearbox to facilitate this.

2. Prohibited modifications: Removal of the synchromesh units from the gearbox is prohibited.

3. Transmissions & Drive ratios: Fiat five speed gearboxes as fitted to transverse engined cars only. Only standard Fiat gears can be used. There must be 81% difference between 1st and 2nd gear. Final Drives:- 4.07 , 3.867, 3.562.

5.10: ELECTRICS

- 1. Exterior Lighting:** Not applicable.
- 2. Rear Warning Light:** An LED rear fog light to EU regulation 7, an FIA homologated LED rear warning light, or an LED stop light to EU regulation 38 is mandatory and must be mounted in accordance with MSA regulations.
- 3. Batteries:** An electrically powered starter motor and battery are mandatory and must be operable by the driver whilst normally seated and must be capable of repetitive starts.
- 4. Generators:** A charging system is optional.

5.11: BRAKES

- 1. Permitted Modifications:** Free, subject to 5.11.2.
- 2. Prohibited Modifications:** ABS is not permitted.

5.12: WHEELS / STEERING

- 1. Permitted Options:** Free.
- 2. Prohibited Options:** Any in contravention of MSA regulations.
- 3. Construction & Materials:** Free.
- 4. Dimensions:** Free.

5.13: TYRES

The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.

- 1. Wet Tyres:** Wet tyres are free but as a minimum the tread pattern must have at least four circumferential grooves of at least 7mm width equally spaced across the tyre and of minimum 1.6mm depth or be a full wet pattern as defined in 6.3.
- 2. Slick Tyres:** Slick tyres must be either the YOKOHAMA crossply, size - 160/515-13. code no: 811/2284 or the YOKOHAMA radial, size 160/520/R13, code no: N2669. Size and code numbers must be clearly visible.

5.14: VEHICLE WEIGHT:


All cars are subject to a minimum weight of 375kg excluding driver and 460kg including driver. Ballast (if required) must be fitted in accordance with MSA regulations J5.15.1 to J5.15.4.

5.15: FUEL TANK / FUEL

- 1. Types:** Free. A non-return valve must be incorporated in the vent system.
- 2. Locations:** Free, subject to MSA regulations.
- 3. Fuel:** Only petrol as defined in Section B Nomenclature & Definitions, Pump Fuel a) section of the MSA Yearbook for the current year and complying with BS4040, BSEN228 or BS7800 may be used; fuel which exceeds the stated RON (max) levels in Appendix 1 of Section B Nomenclature & Definitions is prohibited even if it is sold/promoted as being legal for UK Competition and/or obtainable from 'roadside' pumps. The use of additives by competitors which boost the octane rating (RON) in any petrol is prohibited. At the end of practice and the race at least 3 litres of petrol from the tank of the competing car must be available to the scrutineers for analysis. Compliance with minimum weight for the car will be taken before the petrol is removed.

5.16: SILENCING:

All vehicles must comply with the relevant maximum noise limits set out in MSA Blue Book regulation J. Chart 5.18.



5.17: NUMBERS & CHAMPIONSHIP DECALS

1. Positions: Race numbers must be displayed on each side of the vehicle alongside the cockpit/driver and as far forward on the front of the vehicle as possible. 750 Motor Club decals must be affixed prominently near all number backgrounds. Championship Sponsor's decals (where applicable) must be affixed in or near the positions detailed on the diagram supplied with those decals. 750 Motor Club and Championship Sponsor's decals must take preference to any other decals. Failure to comply will render the vehicle and driver ineligible to race. No decals other than those issued or approved by the 750 Motor Club are permitted. Those currently approved by the Club are:-

BWRDC	750Formula.co.uk
EBC Brakes	Registered Charities
Driver name & blood group	Make & model of car

Additionally, cars in Class C may carry the name of the College on the vehicle.

2. Suppliers: Sponsors and Club decals will be available at the first championship race in which the vehicle is entered.

6. APPENDICES:

Diagram re Cockpit opening (NOT to scale):

ABCD represents the horizontal quadrilateral frame with hinged joints (referred to in 5.6.1.(i)) which has to fit into the cockpit opening. The solid and dotted lines show the frame at the extreme positions, dictated by the internal angles.

Dimensions of the frame are:

AB = 81.3 cms; BC & AD = 45.7 cms; CD = 63.5 cms.

CAMSHAFT SUPPLIER: Cams are available through the club. Please contact: Giles Groombridge, Competitions Manager

The Seven Fifty Motor Club
Donington Park
Castle Donington
Derbyshire
DE74 2RP
Tel: 01332 814548

Wet tyre pattern.

Any wet tyre must have a recognisable tread pattern. This tread pattern is the combination of plain surfaces and grooves extending across the breadth of the tread and round the entire circumference.

The total width of the grooves within the tread pattern when measured across any line within a 20mm circumferential length of the part of the tyre which can contact the road and is parallel to the rotating axis of the tyre and wheel must account for at least 15% of the width of the tread and be at least 1.6mm deep. The orientation of the grooves does not necessarily have to be at 90° to the rotating axis of the wheel/tyre. E.g.

$$\frac{(A+B+C+D+E+F)}{\text{Tread Width}} \times 100 \Rightarrow 15\%$$

