



### 1 SPORTING REGULATIONS: GENERAL

#### 1.1 TITLE & JURISDICTION

The **RGB SPORTS 1000 CHAMPIONSHIP** is organised and administered by Motorsport UK (incorporating the provisions of the International Sporting Code of the FIA) and these Championship Regulations.

- MOTORSPORT UK Championship Permit No: CH2019/R044**
- MOTORSPORT UK Championship Grade: C.**
- Race Status: Clubman/National B.**

#### 1.2 OFFICIALS

**1. Co-Ordinator:** G.Groombridge, Donington Park, Castle Donington, Derbyshire, DE74 2RP

☎ 01332 814548; ✉ giles@750mc.co.uk).

**2. Eligibility Scrutineer:** B. Blackmore

**3. Championship Stewards:**

R.Knight                      K. Messer                      I.Sowman

#### 1.3 COMPETITOR ELIGIBILITY

- Entrants must:
  - be fully paid up valid membership card holding members of the 750 Motor Club and
  - be Registered for the Championship and
  - be in possession of a valid MOTORSPORT UK Entrants Licences.
- Drivers and Entrant/Drivers must:
  - Be current Members of the 750 Motor Club and
  - be Registered for the Championship and
  - be in possession of valid Competition (Racing) National B Licence, as a minimum
  - A professional driver, in possession of a valid Licence (featuring an E.U. flag) and medical, issued by the ASN of a member country of the European Union, or comparable country. ((H)26.2.1. applies)
  - If participation in the Championship requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the Championship. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.
- All necessary documentation must be presented for checking at all rounds when signing-on.

#### 1.4 REGISTRATION

- All competitors must register for the championship by returning the Registration Form with the Registration Fee to the Coordinator prior to the Final Closing date for the first round being entered.
- The Registration Fee for the season is £130 payable upon registration. For competitors wishing to enter a single event a registration fee of £25 is payable **and points will be awarded for this event**. If further races are entered the balance of the £130 fee must be paid.
- Registration numbers will be the permanent Competition number for the Championship
- If any competitor wishes to change to a different car from the one originally registered for the championship, a completed registration form with registration fee must be sent to the Co-ordinator. If the vehicle is in the same class as the one originally registered then, with the approval of the Co-ordinator, championship points already scored may be transferred. If the new vehicle is in a different class, then points will not be transferred.

#### 1.5 CHAMPIONSHIP ROUNDS

The **RGB SPORTS 1000 CHAMPIONSHIP** will be contested over the following rounds:

Date	Circuit	Round/s
13-14 Apr	Brands Hatch (Indy)	2
4 May	Silverstone National	2
15-16 Jun	Anglesey (Coastal)	2
6 Jul	Snetterton 300	2
10-11 Aug	Silverstone International	2
7-8 Sep	Donington Park (National)	2
5 Oct	Oulton Park	2

#### 1.6 SCORING

- Championship points will be awarded to non-invitation competitors listed in the final results for each race as follows:
  - 30, 27, 24, 22, 21, 20, 19, 18, 17, 16, 15, 14, 13, 12, 11, 10, 9, 8, 7, 6, 5, 4, 3.
  - All other finishers - 2.
  - All other starters - 1.
  - Fastest lap - 1-point subject to a minimum of 2 starters.
  - Fastest qualifying lap - 1-point subject to a minimum of 2 starters.
- Additionally, all finishers shall score points in the **RGB Sports 1000 Sporting Cup**. The sporting cup points scored in each race shall be identical to the championship points awarded to the driver. Any driver who, in the course of the year, finishes in the top 3 of an RGB Sports 1000 race will become immediately ineligible for Sporting Cup points in that year and all points that they have scored to that point, and subsequently, will be removed.
- The totals from all qualifying rounds (excluding any races which are abandoned and which are not replaced) less 2 will determine the final championship points positions. Similarly, the totals from all qualifying rounds (excluding any races which are abandoned and which are not replaced) less 2 will determine the final Sporting Cup points positions
- Ties for end-of-season award winning places shall be resolved, when more than one competitor have equal totals, by taking into account the highest number of 1<sup>st</sup> places, 2<sup>nd</sup> places etc from the races they are counting as their best total (i.e. their finishing position in dropped rounds do not get taken into account). If that fails to find a winner their highest or subsequent highest dropped scores will be added to their existing total score until a conclusive result is found.

#### 1.7 AWARDS

- All awards are to be provided by the Organising Club unless agreed otherwise.
- Per Round:
  - Awards for 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> on the track will be given, subject to the number of starters as follows:- 2 to 4 starters -1<sup>st</sup> only; 5 to 7 starters -1<sup>st</sup> and 2<sup>nd</sup> only; 8 or more starters - 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup>.
  - Awards of 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> in the sporting cup will be given, subject to the number of starters as follows:- 2 to 4 starters -1<sup>st</sup> in only; 5 to 7 starters -1<sup>st</sup> and 2<sup>nd</sup> only; 8 or more starters - 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup>.
  - First front-engined car, subject to a minimum of 4 front-engined starters.
  - Driver of the Day, selected by the RGB Sports 1000 committee or their nominated representative for the driver or team member who, regardless of finishing position, most impressed the committee or their representative.
  - Highest placed invitation driver subject to a minimum of four invitation drivers.
- End of year trophies to:
  - 1<sup>st</sup>, 2<sup>nd</sup>, 3<sup>rd</sup>, 4<sup>th</sup>, 5<sup>th</sup> and 6<sup>th</sup> in the overall championship.
  - 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> in the sporting trophy.

- Highest placed front-engined car drivers: 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup>, subject to at least 8 front engined cars competing in at least 5 rounds; 1<sup>st</sup> and 2<sup>nd</sup>, subject to between 5 and 7 front engined cars competing at least 5 rounds; 1<sup>st</sup> only subject to between 2 and 4 cars competing in at least 5 rounds.
  - The RGB Sports 1000 Masters Trophy awarded to the highest placed driver in the championship who was aged 50 or over on 31st December 2018 and who competed in at least 5 rounds of the championship.
  - The RGB Sports 1000 Novice Trophy awarded to the highest placed driver in the championship who was required to wear a novice cross in at least one of the season's championship rounds.
  - The RGB Sports 1000 Technical Innovation Trophy awarded to the driver whose car, in the opinion of a club nominated judge, showed the year's most significant technical innovation.
  - Best prepared car.
- 4. Bonuses:**
- Per Round: Not applicable.
  - Championship: Not applicable
- 5. Presentations:** Garlands and trophies are to be provided for presentation at the end of each race. Prize money and Bonuses shall be posted to the Entrants within one month of the results being declared final after each season.
- 6. Entertainment tax liability:** Not applicable.
- 7. Title to all trophies:** In the event of any provisional results or championship tables being revised after any provisional presentations and such revisions affecting the distribution of any awards the Competitors concerned must return such awards to the 750 Motor Club Competitions Secretary in good condition within 7 days.

## 2 CHAMPIONSHIP EVENT MEETINGS & RACE PROCEDURES

### 2.1 ENTRIES

1. Competitors are responsible for sending in correct and complete entries with the correct entry fee prior to the closing date for entries before each event.
2. Incorrect or incomplete entries (Including Driver to be Nominated Entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Meeting Organiser receives the missing or corrected information or fee.
3. Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Meeting Organisers in writing. D25.1.12. applies.
4. The Entry Fee for each event shall be specified in the SRs and on the entry form.
5. Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.

### 2.2 BRIEFINGS

Organisers should notify competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

### 2.3 QUALIFICATION PRACTICE

1. Should any practice session be disrupted the Clerk of the Course shall not be obliged to resume or re-run the session; the decision of the Clerk of the Course shall be final.
2. Each driver shall complete a minimum of 3 laps in the car to be raced, and in the correct session, in order to qualify (MOTORSPORT UK Regulations Q4.5).

### 2.4 RACES

Should any race be disrupted the Clerk of the Course shall not be obliged to resume or rerun the race ((Q)5.4.) (1.6.4. above applies)

### 2.5 STARTS

1. All cars will be released to form up on the grid prior to the start information as specified on the grid sheet.
2. The start will be via standing start. The minimum countdown procedures/audible warnings sequence shall be:-
  - I. 1 minute to start of green flag/pace lap - start engines/clear grid.
  - II. 30 Seconds - Visible and audible warning for start of green flag/pace lap.
  - III. A five second board will be used to indicate that the grid is complete.
  - IV. The red lights will be switched on five seconds after the board is withdrawn.
3. Any car removed from the grid after the 1 minute stage or driven into the pits on the green flag lap shall be held in the pitlane and may start the race after the last car has passed the startline or pitlane exit, whichever is the later to take the start from the grid.
4. Any driver unable to start the green flag/pace lap or start are required to indicate their situation as per MOTORSPORT UK Regulation (Q)12.13.2. In addition any driver unable to maintain grid positions on the green flag lap, to the extent that ALL other cars are ahead of them, may complete the green flag lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
5. In the event of any starting lights failure the starter will revert to use of the national flag.

### 2.6 SESSION RED FLAG

Should the need arise to stop any race or practice, RED LIGHTS will be switched on at the startline and RED FLAGS will be displayed at the startline and at all marshals signalling posts around the circuit.

This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pit lane, during practice, and to the starting grid area, during a race, unless otherwise directed by officials. Cars may not enter the pits unless directed to do so. Work on cars already in the pits must cease when a race is stopped.

### 2.7 PITS, PADDOCK & PITLANE SAFETY

1. Pits & Paddock: Competitors must ensure that the MOTORSPORT UK, circuit management and organising club safety regulations are complied with at all times.
2. Pitlane: The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all drivers to take all due care and respect the pit lane speed limits.
3. Refuelling: May only be carried out in accordance with the MOTORSPORT UK general regulations, the organising club regulations, circuit management regulations and the SRs or final instructions issued for each circuit/meeting.
4. Speed Limit: Pit lane speed limit will be 60 km/h.

### 2.8 RACE FINISHES

After taking the chequered flag drivers are required to:

- I. progressively and safely slow down
- II. remain behind any competitors ahead of them,
- III. return to the pit lane entrance or paddock entrance as instructed,
- IV. comply with any directions given by marshals or officials
- V. keep their helmets on and harnesses done up while on the circuit or in the pitlane.



### 2.9 RESULTS

All practice timesheets, grids, race results are to be deemed provisional until all vehicles are released by scrutineers after post practice/race scrutineering and/or after completion of any judicial or technical procedures. (MOTORSPORT UK regulation (D)26.3.)

### 2.10 TIMING MODULES

The 750 Motor Club utilises transponder-based timing and competitors must have a compatible transponder fitted and working and advise the race organisers of its number prior to the event. Compatible transponders include the AMB TRANX 260 and MyLaps X2.

### 2.11. QUALIFICATION RACES

If any event is oversubscribed the organising club may at their discretion run qualification races.

### 2.12 OPERATION OF SAFETY CAR

{deleted}

### 2.13 ONBOARD CAMERAS

All competitors are required to carry an on board in car camera with a wide angle lens that records to an SD (or micro-SD) card in a minimum resolution of 960 x 720 pixels. Recordings from the cameras may be used where there is an incident which is subsequently brought before the Clerk of the Course for investigation. The decision to review any such video recording is at the discretion of the Clerk of the Course, the Stewards of the Meeting, the Championship Stewards or the Championship organisers.

- It is the competitor's sole responsibility to ensure safe installation and effective operation of the camera equipment. At all times cameras must be fitted in accordance with MOTORSPORT UK regulations and be approved by the Chief Scrutineer in accordance with J.5.20.5.
- Cameras must be mounted in a central to left position with the steering wheel in clear view.
- In the event that no recording is available on request (other than due to a proven defect with the equipment) sanctions may be applied which can include a 5 place grid penalty if a recording is not available after practice. In the event of recordings not being available after a race sanctions can include time penalties, exclusion from the results and exclusion from the meeting. The burden of proof to establish the cause of any failure will lie with the competitor.

### 2.14 TYRE CHANGING

Although the RGB Sports 1000 championship permits a range of tyres, as defined in 5.13, no changes of the type of tyre (wet or dry) are permitted during a race. That is, once the red lights for the initial start of a race are extinguished then the same type of tyre must be used until the chequered flag is shown.

## 3 SPECIFIC CHAMPIONSHIP REGULATIONS

In the event of any rounds being oversubscribed the organising club may, in liaison with the Championship Coordinator, at their discretion run qualification races as per 2.11 of these regulations. Alternatively at double header race meetings, should there be sufficient space within the timetable, the organising club may divide the grid after qualifying into 3 separate groups. The groups will then form 3 races whereby each competitor participates in two races. All 3 races will be eligible for full championship points.

At each round of the championship race 1 grid positions will be determined by each competitors fastest lap time in qualifying. At double header meetings, the grid positions for race 2 will be determined by the competitors second fastest lap time in qualifying.

## 4 SPECIFIC CHAMPIONSHIP PENALTIES

In accordance with section C of the current MOTORSPORT UK Yearbook and additionally:

## 4.1 INFRINGEMENT OF TECHNICAL REGULATIONS

1. Arising from post practice scrutineering or judicial action:  
Minimum Penalty: The provisions of MOTORSPORT UK Regulations: C3.3.
2. Arising from post race scrutineering or judicial action:  
Minimum Penalty: The provisions of MOTORSPORT UK Regulations: C3.5.1 (a) and (b).  
For infringements deemed to be of a more serious nature the Clerk of the Course will invoke the provisions of regulation C3.5.1 (c).

## 4.2 ADDITIONAL SPECIFIC CHAMPIONSHIP PENALTIES

1. In the case of a driver being excluded from a race, the Clerk of Course will impose the penalties set out in MOTORSPORT UK regulation C3.5.1 a & b and may impose the penalty set out in MOTORSPORT UK regulation C3.5.1 c.
2. In order to maintain standards of conduct, the championship organisers will monitor all officials/observers reports of adverse behaviour at race meetings. If any individual is included on two such reports during one racing season the championship organisers will request the Clerk of Course at future race meetings to consider specific observation of that driver's conduct.
3. The Clerk of Course may impose a "Stop-Go" or "Drive through" penalty during a race in accordance with MOTORSPORT UK Regulation Q.12.6.
4. Any Competitor who is penalized under the Championship Sporting Regulations at any stage of a Championship event and receives an allocation of penalty points on their race license in accordance with MOTORSPORT UK Regulations, will receive a Championship points deduction equal to the number of penalty points which were allocated. Should the same competitor receive penalty points at another round of the Championship then the number of Championship points deducted will be double the number of penalty points applied. If penalty points are applied at a third round, then the Championship points deducted will be triple this number, and quadrupled at the fourth occurrence of such a penalty etc. This may result in a driver receiving a negative score.
5. Championship stewards are also empowered to consider any request from the championship co-ordinator to penalize any competitor for any breach of championship regulations and, after holding a formal hearing if they deem it necessary, to impose a penalty in accordance with MOTORSPORT UK regulation C.2.1.1 (subject to the rights of appeal provided for in Section C.)
6. One or more of the following may be imposed by the championship stewards as appropriate;
  - a) Reprimand.
  - b) Fine. This may also be applied in the case of a driver receiving three reprimands from the Championship Stewards in one season.
  - c) Time or Grid Penalties.
  - d) Suspension from all or part of the championship. This may also be applied in the case of a driver receiving two fines from the championship stewards in one season.

## 5 TECHNICAL REGULATIONS

### 5.1 INTRODUCTION

The following technical regulations are set out in accordance with the MOTORSPORT UK specified format and it must be clearly understood that if the following texts do not clearly specify that you can do it, you must work on the principle that you cannot. The fact that some modifications are mentioned as prohibited does not imply that others are allowed.

### 5.2 GENERAL DESCRIPTION

The **RGB SPORTS 1000 CHAMPIONSHIP** is for competitors participating in two-seater (not tandem) cars powered by a series-production four-stroke motorcycle engine as detailed in 5.7 of these regulations and having a capacity of up to 1000cc.



The engines must have been fitted to production motorcycles manufactured by Honda, Kawasaki, Suzuki or Yamaha and produced prior to:

1/1/09 - Suzuki and Yamaha

1/1/10 - Kawasaki

1/1/12 – Honda (engines with a serial number beginning with SC59E-23 are treated as the same).

Engines may be fitted in the front or rear of the car, providing that the car is compliant with the rest of these regulations.

Entries must be accompanied by the car's current engine number. If an engine is changed during the season the replacement engine number must be provided to the championship coordinator prior to the vehicle competing in a championship event.

In addition, subject to the specific approval of the championship coordinator, the club will permit the entry of drivers in an invitation class. Cars in this class, for example "seven" style cars, would comply with the majority of these regulations but they:

1. may use any standard, unmodified, bike engine,
2. may use any list 1A/1B/1C tyre and
3. must not use any wings, as defined in 5.6.

### 5.3 SAFETY REQUIREMENTS

All cars must comply with the technical regulations listed in the MOTORSPORT UK Year Book Section K & Q, and with the minimum safety requirements listed in section K.

The roll over structure fitted to the car shall provide equivalent protection for both driver and passenger. It is permitted to fit a petty strut that impinges on the space otherwise reserved for the passenger.

Extinguishers must comply with MOTORSPORT UK regulation K 3.1.2 a).

Seat belts must be FIA homologated and as per K2.1.2 , 2.1.3. or 2.1.4; K3, K5, K6, K8 – K14.

Towing eyes must have a minimum internal diameter of 60mm; (note that the towing eye may be of either a suitable rigid or flexible material bolted to the chassis).

### 5.4 GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS

All cars must comply with the requirements of sections J and Q19 of the current MOTORSPORT UK Yearbook.

All vehicles must be of sound construction and mechanical condition and be well maintained. There is no requirement for an MOT certificate, vehicle tax or insurance.

STANDARD: The word 'standard' used within these technical regulations as a description of components is to be interpreted as per 'Standard Part' defined in Section B – Nomenclature & definitions in the MOTORSPORT UK Blue Book. Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance.

As a minimum, two mirrors must be fitted, each with a minimum surface area of 50 sq cms and giving a clear view to the rear, one on each side of the centreline of the vehicle.

### 5.5 CHASSIS

Chassis must be constructed either of a tubular steel spaceframe or an aluminium or steel monocoque. Composite monocoques, or spaceframe chassis which depend on composite panels for their rigidity, are not permitted.

### 5.6 BODYWORK

**a.** Maximum overhang of front bodywork from front wheel axis is 890 mm. Maximum overhang of rear bodywork from rear wheel axis is 850 mm.

**b.** Wings are prohibited, where a wing is defined as a separate part of the bodywork of a car positioned above, behind or in front of the main bodywork and in such a position that air may flow both above and below the part. Diveplanes are prohibited.

**c.** The cockpit area must be enclosed on both sides, floor and bulkheads front and rear. 'Spats' may be fitted in order to comply with MOTORSPORT UK regulation J5.2.6.

**d.** Any forward facing front spoiler/splitter within 15 degrees to the horizontal whether integral with or additional to the original bodywork may not project more than 50mm beyond the plan form of the bodywork where that bodywork is part of the static structure of the car and rises to a height of at least 25mm above the top surface of the floor of the car. A front spoiler/splitter may not exceed the +width of the car across the front wheel arches. In addition, it must form a continuous part of the bodywork.

**e.** For the purposes of these regulations the following terms shall have the following meanings:

- i. 'floor' shall mean the lower surface of the chassis together with any other part of the car which is visible from a point on the ground immediately beneath that point and which is less than 300mm from ground level when the car is resting on the ground at its normal attitude but excluding mechanical components
- ii. 'front floor' shall mean any part of the floor ahead of the front axle line
- iii. 'centre floor' shall mean any part of the floor between the front axle line and the lower edge of the rear bulkhead where it meets the floor
- iv. 'rear floor' shall mean any part of the floor behind the lower edge of the rear bulkhead where it meets the floor
- v. 'mechanical components' shall mean any device which is present on the car for a purely mechanical purpose and is not present and is not designed or shaped in order to have an aerodynamic effect and shall include, but not be limited to, exhaust systems, bolts, nuts, sumps and suspension components
- vi. 'aerodynamic advantage' means the generation of or contribution towards an increase in downforce or a reduction in lift.

The purpose of these regulations is to ensure that RGB Sports 1000 cars have simple floors and do not rely upon the underside of the car to provide an aerodynamic advantage. For the avoidance of doubt, diffusers, vortex generators and any other device attached to the underside or topside of the floor (save as specifically permitted by these rules) which provides or is intended to provide an aerodynamic advantage is not permitted. Your attention is drawn to regulation 5.1 of these regulations.

**f.** The front floor, centre floor and rear floor must be flat laterally (that is, side to side) subject to a tolerance of 10mm. The tolerance permitted of 10mm is to allow for manufacturing tolerances and must not be used to shape any part of the floor to provide an aerodynamic advantage. Any part of the floor shall be treated in this regulation as flat provided that, moving from the centreline of the car to the outer edge of the plan form of the car in a lateral direction, the height of the floor increases or remains constant.

**g.** The centre floor must be flat longitudinally subject to a tolerance of 10mm. The tolerance permitted of 10mm is to allow for manufacturing tolerances and must not be used to shape any part of the floor to provide an aerodynamic advantage.

**h.** The height of the rear and front floors is free (subject to the minimum ride height restriction in paragraph 5 of 'Modifications Permitted') save that they must be flat laterally.

**i.** It is not mandatory to panel the whole or any part of the floor of the car but where any part of the floor is not panelled no part of the floor as defined above may be shaped or designed to provide an aerodynamic advantage. For the avoidance of doubt, any ducts or holes, the purpose of which is to divert air from or to the underneath of the floor of the car, will be treated as part of the floor and are therefore not permitted.

j. It is permitted for mechanical components to extend below the floor of the car (subject to the minimum ride height restriction in paragraph 5 of 'Modifications Permitted') but in this regard your attention is drawn to the definition of mechanical component above.

### 5.6.1 Modifications Permitted

**1. General:** The cockpit perimeter seen in plan view must be symmetrical about the longitudinal axis of the car.

Tandem seating is not permitted.

Cockpit opening must measure at least 81.3cms (32") wide x 71.1cms (28") long.

The bulkhead at the rear of the cockpit and in front of the rear axle shall be a solid panel that, at all heights between the centre floor (as defined in 5.6.e) and the top of the driver's backrest, shall form a continuous horizontal straight line across the width of the driver/passenger compartment. In plan view the bulkhead shall be perpendicular to the longitudinal centreline of the car. **A backrest for the passenger side of the car may be fitted in front of the bulkhead. In plan view this backrest shall, at all heights between the floor and the top of the passenger side bulkhead, be parallel with the bulkhead. In side view the backrest shall be parallel with the bulkhead or slanted further backwards.**

No part of the driver's seat may be behind the bulkhead. Cables, harnesses, pipes, linkages and (in front engined cars) the transmission/propshaft tunnel may pass through the bulkhead, but all holes into the driver/passenger compartment through the bulkhead and passenger backrest must be sealed with a fireproof sealant.

**The length of the space for both driver and passenger shall be measured at the height of the floor along a line parallel with the centre line of the car. The length of the driver's space shall be the distance between the rear bulkhead and the position of a vertical line dropped from the footpad of the undepressed brake pedal to the floor. The length of the passenger space shall be the distance between the front of the space usable by the occupant's feet and the rear bulkhead or backrest, whichever is the shorter. The length of the passenger space must be at least 75% of that provided for the driver. The width of the space for the passenger's feet shall be at least 150 mm.**

Only a fire extinguisher, battery, roll bar bracing and other minor components may impinge on the passenger space. **For the avoidance of doubt a fuel tank is not a minor component.**

The perimeter of all lateral sections of the chassis between, and including, the rear bulkhead (as defined above) and the forward end of the passenger space shall, with the exception of any roll-over or safety related structure intended to limit intrusion into the car, be symmetrical about a vertical plane that extends the longitudinal centre line of the car. A tolerance is allowed here in that when a measurement is made on one side of the centre line of the car then a similar measurement on the other side of the car shall be the same within a given tolerance. This tolerance shall be +/- 25mm with the single exception of the top parts of the chassis adjacent to the driver's outer shoulder for which the tolerance shall be +/- 50mm.

Specific cars that ran in the 2016 race season (see Appendix 1) are not required to comply with this regulation during the 2018 and 2019 seasons. However, any such cars using this exception shall be fitted with bodywork that would fit a chassis that does comply with this regulation. For the 2020 season and beyond no such consideration shall apply.

The centreline of the driver's seat must be at least 25.4cms (10") from the longitudinal centreline of the car. The centreline of the seat is defined to be that line along the floor of the car which is a vertical projection of the line from the centre of the top of the seat to a point midway between the two crotch straps as they penetrate the seat when the driver is seated and strapped in.

**2. Interior:** It is permissible to remove interior trim and passenger seat.

**3. Exterior:**

**ALL VEHICLES:** The engine and transmission must be fully enclosed. It is permitted for the air exit from a front-mounted radiator to exhaust through the top surface of the bodywork without any covering but the ducting between the bodywork and the radiator must ensure that the radiator hoses and piping are fully shielded from this ducting.

Tonneau covers are not permitted.

Any car fitted with a soft-top or hardtop will be considered to be a closed car and must be fitted with a full width and height windscreen and rear screen.

**FRONT ENGINED CARS:** Air filters may protrude through the bonnet without the need for any cover but must have an effective seal between them and the bonnet; any other holes in the upper surface of the bodywork forward of the steering wheel plus any holes in the side surfaces of the bodywork forward of the steering wheel above a longitudinal line joining the top of the front and rear wheel rims ("engine cover holes"), must be covered with solid bodywork having only a forward facing opening, forward facing louvres or with a metallic gauze with a maximum hole size of 1mm. Holes solely for the exhaust system do not require any cover/gauze but must be a reasonably close fit. The total area of non-forward facing engine cover holes (excluding properly ducted radiator exhausts as described in this section) must not exceed 400 cm<sup>2</sup>.

### 4. Silhouette:

**5. Ground Clearance:** For the purposes of these regulations 'test conditions' are defined as: Normal racing trim with fluids and driver aboard in racing attire, as if the car has or is about to take part in a track session and the ride height has not been subjected to external influences. Testing may take place in the pitlane, parc fermé or the scrutineering bay.

During test conditions under no circumstance can any part of the bodywork, or of the suspended part of the car with the exception of the exhaust system, be below a horizontal plane passing 75mm (50mm for exhaust systems) above the ground. A gauge of 75mm or 50mm may be used by scrutineers before or after races or practice to check the ground clearance. There is no negative tolerance to these measurements.

The scrutineers may choose to apply an additional load test to the car in test conditions. A weight of 75Kg or more may be applied to the car's chassis and subsequently removed prior to testing (in practise this will be a scrutineer standing in the passenger space). The car may be moved to allow for bearing stiction to be eliminated, which must be initiated by the scrutineer; no other form of intervention is permitted to allow the vehicle to return to its rest position using the suspension springs only. Subsequently, the car's ride height may be rechecked.

### 5.6.2 Modifications Prohibited

**1. General:** Any in contravention of 5.6.1.

**2. Interior.** It is not permitted to mount the fuel tank/s within the driver/passenger space.

**3. Exterior:** No wings are permitted where a wing is defined as in 5.6.

### 4. Silhouette:

**5. Ground Clearance:** Side skirts or bridging devices are not permitted.

## 5.7 ENGINE

Any production four stroke motorcycle engine manufactured by Honda, Yamaha, Kawasaki or Suzuki and with manufacturer's quoted capacity and date of production as per 5.2. If requested the competitor must supply manufacturer's official literature with registration to prove compliance with this regulation.

Two stroke engines or multi-engine installations are not permitted.

The engine must remain entirely standard – your attention is drawn to 5.1. As the engine is standard preparation of the engine must be restricted to those modifications that do not add or remove metal from the engine internals.

It is permitted to remove the standard coolant pump and oil/coolant intercooler if fitted as standard.

It is permitted to obscure any ports used on the standard engine for air injection into the exhaust system.

Camshafts, their drive sprockets and connecting bolts must be standard and unmodified. Where slots are provided in camshaft sprockets in addition to circular timing holes, only the holes are to be used for timing the camshaft. The slots must not be used for any location purposes. In engines where the timing is set by the sprocket not having any positive location on the camshaft (e.g. the Suzuki engine), valve timing must be in accordance with standard manufacturers' settings.

The wiring loom/harness is free.

Crankcase breathing is free.

Limited Edition engines are not permitted.

The lubrication system is free and may have the oil pickups and drain holes modified to suit the installation. Dry sump systems, modified sumps and pick-up pipes are permitted. Oil coolers are permitted provided they are within the overall periphery of the vehicle.

### 5.7.1 Modifications Permitted

As per 5.7.

### 5.7.2 Modifications Prohibited

Any other than those permitted in 5.7.

### 5.7.3 Oil and engine cooling

Any system may be used for oil and engine cooling provided radiators are within the periphery of the vehicle. Waterless coolant is permitted.

Oil hose connectors must be either swaged fittings, 'Aeroquip' – type compression fittings or good-quality high-pressure fittings. (The use of hose-clips on oil pipes is prohibited due to the extreme pressures developed by bike engines.)

### 5.7.4 Induction Systems

Air filtration system is free.

The induction system must be standard for the engine being used, though jetting on carburettors is free. The boundary between the induction system and the air filtration system is defined to be at the entry to the throttle body or carburettors. Hence, aftermarket velocity stacks are permitted.

### 5.7.5 Exhaust systems

Exhaust systems including manifold are free but must comply with MOTORSPORT UK noise restrictions as per MOTORSPORT UK yearbook J5.16.5 & 5.17.

### 5.7.6 Ignition systems

1. The standard ECU's rev-limiter must remain in operation with standard manufacturers settings, and be the only non-mechanical means of controlling engine speed (excepting functions of the standard ECU for the engine). Ignition-cutting systems other than the standard rev-limiter are not permitted. The standard ECU for the engine must be used as the main control of engine management.

The standard ECU must not be modified in any way; in particular it is not permitted to change the ignition, fuel or any other mapping or configuration in any way. The 750 Motor Club reserves the right to remove and test ECUs or to exchange the ECU in any specific car, for the duration of a race or an entire meeting, for an equivalent manufacturer's standard unit. Failure to comply with such an exchange request will render the car in question ineligible to compete at the meeting in question.

Competitors are required to make their own ECUs available for swapping to facilitate these checks. As such it must be straightforward to remove and replace the ECU, along with any item keyed to the ECU such as an ignition key. All competitors' ECUs so used will be labelled with their name using non removable labels provided by the 750 Motor Club. The competitor's own ECU will be returned to them at the conclusion of the meeting.

2. The use of a single approved 'piggy-back' device, in conjunction with the standard ECU, to modify fuelling only is permitted provided it does not contravene the remainder of 5.7.7. Approved piggy-back devices are the Dynojet Power Commander PCII, PCIII, PCIIIr, PCIIusb (fuel module only) and PCV (fuel injection module only). Note that the use of a PCV module that incorporates ignition timing mapping, or any separate ignition mapping module, is not permitted.

3. The standard ECU and any piggy-back device should be easily accessible for scrutineering purposes and for affixing the championship ECU seals. Any manufacturer markings on the ECU and any piggy-back device must remain intact and easily visible.

4. The 750 Motor Club reserves the right to install a logging device in any RGB Sports 1000 car during pre-race scrutineering and to access that device in post-race scrutineering, where such a device is intended to check compliance with the rest of these regulations.

5. The engine's ignition timing must always be in the control of the original ECU's ignition maps and any standard engine components such as trigger wheels and position sensors. The use of a device, such as the Dynojet IRC and wiring so as to convince the ECU that it is always in 6th gear, is permitted if that device merely assists the ECU in selecting sites in the standard ignition maps.

6. All engines must be fitted with a minimum of two cam cover bolts cross drilled with a 1.5mm hole to allow the official RGB Sports 1000 Championship wire seals to be inserted. These drilled bolts must be such that the bolts and seal are easily visible for inspection by scrutineers.

7. It is mandatory that all cars in a race have engines and ECUs that are sealed using the drilled bolts and seals as above. These seals will either be applied by the club's scrutineers or, should the competitor have previously taken the car to one of the approved dynamometer centres listed in Appendix 2, by the dynamometer operator. If the latter is the case, the operator will supply details of the test results, engine number and seal numbers to the championship co-ordinator.

8. The 750 Motor Club reserves the right to request that competitors (as nominated by club officials) must complete a power run on a dynamometer before a specific upcoming race. The dynamometer in question could either be one provided at the club's expense at a race meeting or one of those nominated in Appendix 2 to these regulations. Failure to comply may result in exclusion from the upcoming meeting. In either case, details of the test results, engine number and seal numbers will be supplied to the championship co-ordinator.

9. The standard loom's diagnostic connector is required to be available for ease of connection of ECU analysis equipment. An in-car gear indicator may be connected to the diagnostic connector as long as it is easily removable for scrutineering purposes.

10. Any electronic module related to the engine and present in the car is required to be connected to the engine at all times during qualifying and racing.

### 5.7.7 Fuel delivery systems

Fuel pump and fuel lines are free, subject to MOTORSPORT UK

## 5.8 SUSPENSION

1. **Permitted modifications:** Suspension systems are free, subject to MOTORSPORT UK regulations.

2. **Prohibited modifications:** Active suspension is prohibited.

No suspension components of composite construction are permitted.

**Suspension must be provided by coilover damper units which must be limited to, at the most, 3 way adjustability.**

**It shall not be possible for any suspension adjustment (for example ARB setting, damping rates or any adjustment that affects ride height) to be made by the driver from within the cockpit.**

3. **Wheelbase/track:** Free.

## 5.9 TRANSMISSION

The gearbox must be standard to the engine.

There must be a means of reverse, which may be internal or external to the gearbox; this must be operable by the driver whilst normally seated. Cars will be required to drive in reverse a minimum distance of 3 metres on the flat during which one of the wheels will be required to pass over a block 40mm square.

### 5.9.1 Permitted modifications

Drive may be either by propshaft or chain.

Gear position electronic sensor: The gear position sensor to the ECU, if fitted, must be permanently disabled or permanently enabled; it is not permissible for it to be switchable.

Clutch: Clutch plates are free. Steel reinforcing bands may be fitted around the outside of the clutch basket. Clutch springs may be uprated. Clutch operation may be hydraulic or mechanical but must be under direct control of the driver with no electrically or electronically controlled assistance.

### 5.9.2 Prohibited modifications

Gear selection, clutch and throttle operation must be purely mechanical and solely under direct control of the driver. The gear linkage and clutch system must be purely mechanical (hydraulic clutch systems are permitted). No electrical connections, switches or sensors may operate on any part of the clutch or gear controls or linkages. Note that this implies that "flatshifters" are not permitted in any form.

Four-wheel drive is not permitted.

Electronic traction control is not permitted.

### 5.9.3 Transmission and Final Drive ratios

**Gearbox ratios must remain as standard. Final drive ratio is free. A limited slip differential may be fitted and are restricted to a Quaife ATB, a Radical reversing transmission or a Ford Sierra viscous unit.**

## 5.10 ELECTRICS

### 5.10.1 Exterior Lighting

This must consist of at least the following:

- A pair of forward facing white main beam lights positioned towards the front of the car and one near to each side of the car.
- A pair of red tail lights, clearly visible to following drivers, and positioned at the rear of the car with one on each side of the car.
- A pair of red brake lights, clearly visible to following drivers and positioned at the rear of the car with one on each side of the car.
- Indicator lights positioned on each corner of the car and easily visible to drivers in front and behind.

### 5.10.2 Rear Warning Light

An LED red warning light compliant with MOTORSPORT UK Yearbook Regulation J.5.1 is mandatory and must be mounted directly to the rear or the underside of the rear roll hoop, within 10cms of the centreline of the vehicle. Where high bodywork behind the rollcage may prevent the light being fully visible, the light may be fitted to the rear of that bodywork at an equivalent height within 10cms of the centreline of the car. Any manufacturer fitted rear fog light must be disabled.

### 5.10.3 Battery and starter

A battery and starter motor capable of repetitive starts must be fitted and operable by the driver whilst normally seated.

### 5.10.4 Charging system

The standard engine's alternator/generator must be fitted and electrically connected so that the standard battery charging function is providing a charge to the onboard battery. All phases of the standard alternator/generator must be fully functional.

## 5.11 BRAKES

A parking brake mechanism must be fitted that permits the car to be held in position such as on a sloping race circuit grid.

### 5.11.1 Permitted Modifications

Free.

### 5.11.2 Prohibited Modifications

ABS systems are prohibited.

Brake rotors must only be of steel or iron construction.

**Brake calipers must have a maximum of 4 pistons and have a body constructed of aluminium or steel.**

## 5.12 WHEELS / STEERING

### 1. Permitted Options:

**2. Prohibited Options:** Four wheel steering is not permitted. The fitment of any 'wheel trims' or similar air deflectors is prohibited.

### 3. Construction & Materials:

**4. Dimensions:** Wheels: Max width 7".

## 5.13 TYRES

**1. Specifications:** The only permitted tyres for the RGB Sports 1000 championship are the Yokohama A048 compound M or MH and the Avon CR28 Sport. Entries to the invitation class are permitted to use any list 1A, 1B or 1C tyre. No alteration to the tyre from the manufacturer's or supplier's specification or pattern is permitted.

### 2. Nominated Manufacturers for championship tyres:

Yokohama, Avon.

**3. Suppliers:** Tyres will be available, if pre-ordered, at most race meetings from Polleysport – 01354 688111.

**4.** The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.

**5. All Yokohama A048 tyres must be barcoded (see example below). Tyres purchased through Polleysport will be automatically barcoded, if purchased elsewhere barcodes will be available from Polleysport at additional cost. There is no requirement for Avon CR28 tyres to be barcoded.**

**Drivers will only be permitted to use a total of 14 Yokohama A048 tyres during the course of the season. The number of Avon CR28 tyres used is not restricted.**

**Drivers will be required to nominate which Yokohama A048 tyres they are using at each race weekend when they present the car at scrutineering, this will be done via a tyre information form listing the barcode identification numbers of the driver's chosen tyres. Any competitor found during post qualifying/race scrutineering, to have qualified or raced with a tyre not listed on the 'Tyre Record Form' or to have exceeded their allotted number of tyres will be disqualified from the results and may be subject to further penalties. Tyres are not transferable between drivers.**



Example bar code.

## 5.14 VEHICLE WEIGHT

Minimum weight including driver with helmet, race overalls etc is:-

**Front engined car:** 550kg.

**Mid/rear engined car:** 580kg.

The 750 Motor Club reserves the right to change any of these minimum weights, after rounds 3, 6 & 9, giving 7 days' notice.

Any ballast needed to satisfy these weight regulations shall be fitted in the car in agreement with MOTORSPORT UK Yearbook Regulation J.5.15.4.



### 5.15 FUEL TANK AND FUEL

**1. Types:** Fuel tanks are free but safety tanks are recommended. A non-return valve must be incorporated in the vent system. Fuel tank capacity must be sufficient to allow the car to race for at least 30 minutes plus one lap, after which the car must comply with 5.15.3.

**2. Locations:** Position free subject to MOTORSPORT UK regulations.

**3. Fuel:** Only fuel as defined in Section B Nomenclature & Definitions, Pump Fuel a) section of the MOTORSPORT UK yearbook for the current year and complying with BS4040, BSEN228 or BS7800 may be used; fuel which exceeds the stated RON (max) levels in Appendix 1 of Section B Nomenclature & Definitions is prohibited even if it is sold/promoted as being legal for UK competition and/or obtainable from 'roadside' pumps. The use of additives by competitors which boost the octane rating (RON) in any petrol is prohibited. At the end of practice and the race at least 3 litres of fuel from the tank of the competing car must be available to the scrutineers for analysis. Compliance with minimum weight for the car will be taken before the fuel is removed.

### 5.16 SILENCING

All vehicles must comply with the relevant maximum noise limits set out in MOTORSPORT UK Year book regulation J. Chart 5.18.

### 5.17 NUMBERS AND CHAMPIONSHIP DECALS

These regulations apply to the race numbers and other decals that are required to be carried on cars. Failure to comply with these regulations will render the vehicle and driver ineligible to race.

**1. Race numbers:** Race numbers and backgrounds, in accordance with MOTORSPORT UK Yearbook Regulations J.4 must be displayed on each side of the vehicle alongside the cockpit/driver and as far forward on the front of the vehicle as possible. 750 Motor Club decals must be affixed prominently near all number backgrounds.

**2. Championship sponsor's decals:** Unless specified otherwise by the sponsors such decals must be displayed on each side and towards the front of the car. 750 Motor Club and Championship Sponsor's decals must take preference to any other decals. Failure to comply will render the vehicle and driver ineligible to race.

**3. Championship decals:** If available, championship decals must be displayed on both sides and at the front of all cars.

**4. Suppliers:** Sponsors, championship and club decals will be available at the first championship race in which the vehicle is entered.



### Appendix 1

Mittel Cars – MC53 – 003  
Mittel Cars – MC53 – 004

### Appendix 2

#### Championship Nominated Dyno Centres:

##### **PDQ Motorcycle Developments**

Marshgate Trading Estate  
Hitcham Road  
Taplow  
Berkshire  
SL6 0LX  
01753 730043  
sales@pdq1.co.uk  
www.pdq1.com

##### **HLM Tuning (Bromsgrove)**

Units 1-2  
Factory Lane  
Bromsgrove B61 7AL  
01527 577710  
info@hlmtuning.co.uk  
www.hlmtuning.co.uk

##### **Daytuner Performance Ltd**

Unit 1a Killinghall Stone Quarry  
Ripon Road  
Harrogate  
North Yorkshire  
HG3 2BA  
01423 523 323  
info@daytuner.co.uk  
www.daytuner.co.uk